



SMA DATA MANAGER M

EDMM-US-10



ennexOS
CROSS SECTOR ENERGY MANAGEMENT

Fast and simple

- Quick and intuitive commissioning including Sunny Portal registration
- Simple integration of I/O systems and energy meters

Future-proof and flexible

- Can be flexibly expanded to satisfy new requirements and changing customer needs via software expansion packs
- Provides a gateway to the rapidly changing energy market of the future

Reliable and convenient

- Complies with international grid integration requirements
- Detailed analytics, alert system and reporting


Lowest risk solution

- Secure remote monitoring and control of all connected components
- SMA recently named the #1 global provider of monitoring and energy management solutions by Navigant and GTM Research

SMA DATA MANAGER M

A new dimension of energy monitoring and management

In combination with the new Sunny Portal powered by the award-winning ennexOS, the Data Manager M optimizes communication, monitoring and control of PV systems. The Data Manager M replaces the SMA Cluster Controller and brings the new ennexOS software platform based on the Internet of Things (IoT) for energy management. It is both easily expandable and well equipped to address the new energy business models of the future. With intuitive setup functions for the Data Manager M and inverter, commissioning time and associated labor is significantly reduced. And with the new ennexOS platform, system and inverter parameters can be changed remotely via Sunny Portal, further reducing OPEX costs. The Data Manager M powered by ennexOS is the ideal energy management solution for system owners and operators alike.



Technical data	SMA DATA MANAGER M
Communications	
Supported devices	Max. 50 devices: Inverters, I/O systems & meters, Ethernet, 100 Mbit/s
Connections	
Voltage supply	2-pin connection, MINI COMBICON
Network (LAN)	2 x RJ45, switched, 10BaseT/100BaseT
USB	1 x USB 2.0, type A
Voltage supply	
Voltage supply	External power supply unit (available as an accessory)
Input voltage	10 V to 30 V
Power consumption	Typically 4 W
Ambient conditions in operation	
Environment	Restricted class 3K7 reg. IEC60721-3-3
Ambient temperature	-4 °F to +140 °F
Permissible range for relative humidity (non-condensing)	5% to 95%
Maximum operating altitude above MSL	0 m to 3,000 m (≥70 kPa)
Degree of protection according to IEC 60529	IP20
General data	
Dimensions (W / H / D)	6.36 inch / 3.53 inch / 2.65 inch
Weight	0.5 lb
Mounting location	Indoors
Mounting type	Top-hat rail mounting / wall mounting
Status display	LEDs for system and communication status
Features	
Warranty	2 years
Certificates and approvals (more available upon request)	www.SMA-Solar.com
Accessories (optional)	
Top-hat rail power supply unit	Input: 100 V to 240 V AC / 45 Hz to 65 Hz Output: 24 V DC / 2.5 A
I/O system by Moxa Europe GmbH	ioLogik E1242 (4AI/4DI/4DIO), SMA order number: eIO-E1242 ioLogik E1260 (6RTD), SMA order number: eIO-E1260
I/O system by WAGO Kontakttechnik GmbH & Co. KG	WAGO I/O SYSTEM 750 (8DI, 8DO, 4AI, 4AO, 2RTD), SMA order number: eIO-750Bundle
Type designation	EDMM-US-10

EDMM-US-101 E2620 SMA and ennexOS are registered trademarks of SMA Solar Technology AG. Printed on FSC-certified paper. Changes to product and services, including those resulting from country-specific requirements, and deviations from technical data are subject to change without notice. SMA assumes no liability for errors or omissions. For the latest information, go to www.SMA-Solar.com